

# MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*

---

## 1 IDENTIFICATION OF PREPARATION IDENTIFICATION OF MANUFACTURER AND DISTRIBUTOR

---

**Identification of Preparation:**

**INTER TROTON MASTER  
MATT BLACK**

**Application:**

Professional repairs of car body repairs.

**Manufacturer/Distributor:**

TROTON Sp. z o. o.  
78-120 Gościno  
Ząbrowo 14A, Poland

tel/fax +48 94 35 126 22  
tel +48 94 35 123 94  
e-mail: [troton@troton.com.pl](mailto:troton@troton.com.pl)

**Emergency telephone number (8:00 am – 4:00 pm):** +48 94 35 126 22

**Person is responsible for making this Safety Material Data Sheet: Katarzyna Romanska e-mail:**  
[k.romanska@troton.com.pl](mailto:k.romanska@troton.com.pl)

Date of preparation: August 1<sup>th</sup>, 2006

Revision date: December 7<sup>th</sup>, 2007

---

## 2 IDENTIFICATION OF THREATS

---

### 2.1 Classification and marking of preparation

Product extremely flammable(R12).  
Irritating product (Xi). Irritating to eyes(R36).  
Repeated exposure may cause skin dryness or cracking.(R66).  
Vapours may cause drowsiness and dizziness (R67).

### 2.2 Fire hazard

Aerosols under pressure,extremely flammable.Components with air forming explosive mixtures.  
In case of activity of higher temperature container may undergo unsealing with emission of gases and aerosols.

---

## 3 CHEMICAL COMPOSITION AND INFORMATION CONCERNING INGREDIENTS

---

### 3.1 Dangerous ingredients of the mixture and their classification

<u>Compound:</u>	<u>EEC No.</u>	<u>CAS No.</u>	<u>WE No.</u>	<u>% by weight</u>	<u>Symbol</u>	<u>R Phrases</u>
Acetone	606-001-00-8	67-64-1	200-662-2	25-50	Xi; F	11-36-66-67
Butane	601-004-00-0	106-97-8	203-448-7	10-25	F+	12
Propane	601-003-00-5	74-98-6	200-827-9	10-25	F+	12
N-butyl acetate	607-025-00-1	123-86-4	204-658-1	5-10		10-66-67
2-methoxy-1-methylethyl	607-195-00-7	108-65-6	203-603-9	2,5-<5	Xi	10-36

---

# MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*

acetate						
Propan-2-ol	603-117-00-0	67-63-0	200-661-7	≤ 2,5	Xi; F	11-36-67
Solvent naphtha (petroleum), heavy arom.	649-424-00-3	64742-94-5	265-198-5	≤ 2,5	Xn	65-66-67
Solvent naphtha (petroleum), light arom.	649-356-00-4	64742-95-6	265-199-0	≤ 0,5	Xn; N	10-51/53-65-66-67

---

## 4 FIRST AID MEASURES

### 4.1 Instruction of proceeding, depending on the way of exposure:

Inhalation:	remove the affected person to fresh air, keep calm, cover with a blanket. If shortness of breath occurs, give oxygen. If breathing has stopped, administer artificial respiration and get medical advice.
Eye contact:	remove contact lenses. Flush immediately with plenty of water during 15 minutes, holding the eyelids wide open. Consult an ophthalmologist.
Skin contact:	immediately flush with plenty of water, take off all contaminated clothing, wash skin with plenty of water and soap. In case of any irritation, consult a doctor.
Ingestion:	If swallowed, do not induce vomiting because of risk of inhalation into lungs. Seek medical advice immediately.
General recommendations:	take normal precautionary measures applied during work with chemicals. In case of any alarming symptoms, seek medical advice.
Notes for doctors:	no special antidote, apply symptomatic treatment.

---

## 5 PROCEEDING IN CASE OF FIRE

### 5.1 Personal protection means:

Working clothes made of dense fabric, gloves made of material resistant for organic solvents, shoes made of material resistant for organic solvents, safety goggles in tight casing, respiratory protection against solvents vapors and dust (brown color, marked with "A" letter with P2 filter, marked with white color).

### 5.2 Detailed guidelines:

Remove all potential sources of ignition, tighten damaged packing, place the enamel collected from environment in substitute packing. Collected substance should be transferred to destruction.

### 5.3 Precautions within environment protection range:

Safeguard sink-holes. In case of contamination of waters, immediately notify the relevant authorities. Contaminated soil should be removed together with greenery, covering the soil treating it as collected enamel. Similarly proceed with used packing.

### 5.4 Utilization methods:

Burning in specially appointed installations – after emptying of packing, according to requirements, concerning explosives. Do not discharge extinguishing medium to sawage system

---

## 6 PROCEEDING IN CASE OF UNINTENTIONAL RELEASE TO ENVIRONMENT

---

# MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*

## 6.1 Protection of humans

Working clothes made of dense fabric, gloves made of material resistant for organic solvents, shoes made of material resistant for organic solvents, safety goggles in tight casing, respiratory protection against solvents vapors and dust (brown color, marked with "A" letter with P2 filter, marked with white color).

## 6.2 Detailed guidelines concerning storage conditions:

All storage rooms should be well ventilated because of creation of explosive mixtures with air. Electric installation should fulfill explosion-proof requirements.

## 6.3 Protection of environment

Prevent penetration into sewage system, soil, underground and surface water. In case the product penetrates into sewage system or water, notify applicable authorities immediately.

## 6.4 Methods of neutralisation, collection and environment cleaning

Absorb spilled product with chemically neutral absorbing material (sand, diatomaceous earth), transfer to tight containers and deliver to authorised disposal agent.

---

## 7 HANDLING PREPARATION AND STORE CONDITIONS

### 7.1 Poisoning prevention:

During all works, connected with enamel, one should not eat, drink, take any drugs, avoid direct contacts, avoid breathing of dusts and aerosols, and observe the principles of personal hygiene.

### 7.2 Detailed guidelines concerning storage conditions:

All storage rooms should be well ventilated because of creation of explosive mixtures with air. Electric installation should fulfill explosion-proof requirements.

### 7.3 Storage:

Preparation must be stored in properly marked factory packs, provided with information in Polish, according to operative standards and regulations. Storage rooms should be adopted to storage of flammable and harmful substances. All sources of ignition including electrostatic voltage should be eliminated. The storage temperature must not exceed 20°C. Protect against direct sunlight and sources of temperature, exceeding 50°C. Store in separation with oxidizing and deoxidizing materials.

### 7.4 Methods of proceeding with waste:

The lacquer in aerosol is considered as waste if it can not be used in any form. The waste enamel should be transferred to the area indicated by environmental protection authority in purpose of emptying the packing and subsequent liquidation by burning.

---

## 8 EXPOSURE CONTROL AND MEASURES OF INDIVIDUAL PROTECTION

### 8.1 Technological means of exposure limitation

General means – indispensable for proper transport, storage and using the acrylic enamel in aerosol.

### 8.2 Values of NDS<sup>1</sup>, NDSCh<sup>2</sup>, NDSP<sup>3</sup>

---

<sup>1</sup> NDS –The Maximum Permissible Concentration

<sup>2</sup> NDSCh -The Maximum Permissible Momentary Concentration – the average value of concentration which should not result the negative changes of worker's health, if exists in work environment not longer than 15 minutes and not more frequently than two times per working shift in time interval not shorter than one hour.

# MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*

<u>Składnik</u>	<u>CAS - nr</u>	<u>Normatyw</u>	<u>wartość</u>	<u>Jednostka</u>
acetone	67-64-1	NDS	600	mg/m <sup>3</sup>
		NDSch	1800	mg/m <sup>3</sup>
propane	74-98-6	NDS	1800	mg/m <sup>3</sup>
		NDSch	---	mg/m <sup>3</sup>
butane	106-97-8	NDS	1900	mg/m <sup>3</sup>
		NDSch	3000	mg/m <sup>3</sup>
butan-1-ol	71-36-3	NDS	50	mg/m <sup>3</sup>
		NDSch	150	mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate	108-65-6	NDS	260	mg/m <sup>3</sup>
		NDSch	520	mg/m <sup>3</sup>
N-butyl acetate	123-86-4	NDS	200	mg/m <sup>3</sup>
		NDSch	950	mg/m <sup>3</sup>
Dimethyl ether	115-10-6	NDS	1000	mg/m <sup>3</sup>
		NDSch	---	mg/m <sup>3</sup>

Legal basis:

Order of Minister of Labor and Social Policy of November 29<sup>th</sup>, 2002 on behalf of concentrations and intensity of harmful factors in working environment (Law Gazette, No. 217, item 1833, 2002 with later amendments).

## 8.2 Personal Protection Measures

### **Hands:**

Gloves made of material resistant for organic solvents;

### **Eyes:**

Safety goggles in tight casing (casing made of plastic resistant for organic solvents);

### **Respiratory system:**

Respiratory system protection in case of work in the atmosphere with enamel (including particle filter, marked with white color and "P 2" symbol and organic vapors filter, marked with brown color and marked by letter "A");

### **Skin and body:**

Protective clothes made of dense fabric and protective apron.

### **Collective protection:**

Ventilation in working posts in closed areas;

### **Other information:**

**Industrial hygiene:** General regulations concerning industrial hygiene are valid. One ought to avoid the direct contact of body and respiratory tract with the enamel. Contaminated clothes should be replaced.

After completion of work one ought to wash scrupulously the skin. During work do not drink, eat and do not take drugs. Remove the enamel which was released to environment.

**Threats prevention:** Where there occurs the possibility of dangerous concentrations of vapors and aerosols, one ought to establish the water sprinklers. Sewage, considered as toxic ones should be collected and properly processed.

One ought to wear protective clothes, shoes, protective coat and gloves.

---

<sup>3</sup> NDSP -- The Maximum Permissible Threshold Value of concentration, which, due to threat for worker's health or life can not be exceeded in working environment in any moment.

# MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*

## 9 PHYSICAL & CHEMICAL PROPERTIES

---

### 9.1 Physical form, color, smell and taste:

Aersol, black

### 9.2 Pressure in temperature of 20°C

8300 hPa

### 9.3 Solubility in water:

droppable

---

## 10 STABILITY AND REACTIVITY

---

### 10.1 Stability and reactivity:

In normal conditions the product is stable in duration of 24 months.

### 10.2 Materials causing the hazard:

Avoid contact with aggressive oxidizers (e.g. hydro peroxide, perchlorates, peracetates and permanganates).

### 10.3 Corrosive properties:

Weak, especially in presence of moisture.

---

## 11. TOXICOLOGICAL INFORMATION

---

### 11.1 Tracts of exposure:

- breathing;
- engorgement;
- contact with skin;
- contact with eyes.

### 11.2 Local effects:

**Breathing** – There appears the shortening of breathe accompanied by cough. Vapors of organic solvents are quickly absorbed by lungs, causing the same symptoms as after engorgement.

**Engorgement** – There appear symptoms of acute irritation of mucous membranes of digestive tract, nausea, vomiting and diarrhea. Absorption in organism results in headache, feeling of fatigue, sleepiness, cardiac arrhythmia, disturbances in central nervous system, hepatic and nephrogenic failures.

**Contact with skin** – No Irritation, redness and skin drying-up may appear.

**Contact with eyes** – Irritation, burning, redness and epiphora may appear.

### 11.3 Health results in case of acute exposure:

After-effects of acute intoxication by organic solvents being present in paint: irritation of mucous membranes of eyes and respiratory tract, feeling of fatigue, vertigo, headache, disorders of bodily equilibrium, nausea, vomiting and insomnia.

### 11.4 Health results of chronic exposure:

Persons, who are chronically exposed to risk of breathing the air contaminated by vapors originated from this preparation, may complain for irritation of mucous membrane, headaches and vertiginousness, excitement or drowsiness, problems with alimentary system and skin exsiccation.

---

## 12. ENVIRONMENTAL INFORMATION

---

**No data available concerning mobility in environment, biodegradation and bioaccumulation of product.**

### 12.1 Ecotoxicological data concerning ingredients of product:

# MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*

<b>Acetone</b> LD50 (rat intramuscular) – 5800 mg/kg	<b>Monobuthyl ether of ethylene glycol</b> LD50 (rat intramuscular) – 2125mg/kg
<b>Butane</b> LC50 (rat inhalation) – 658 g/m <sup>3</sup> /4h	<b>Xylene</b> LD50 (rat orally) – 4300 mg/kg

## Detailed marking:

Pressurised container. Do not expose to temperatures in excess of 50°C. Protect from direct sunlight. Do not pierce or burn even after use. Do not use near flames or incandescent materials. Do not smoke during spraying. Keep away from children.

**Contains: Propane/butane/isobutene mixture Acetone, Butane , Monobuthyl ether of ethylene glycol , Xylene , Toluene**

## Legal basis:

Act, dated April 27<sup>th</sup>, 2001 about wastes (Law Gazette, No. 62, item 628, 2001);

Order of Minister of Environment, dated September 27<sup>th</sup>, 2001, on behalf of catalog of wastes (Law Gazette No. 112, item 1206, dated October 8<sup>th</sup>, 2001);

Act, dated May 11<sup>th</sup>, 2001 on behalf of packing and pack wastes (Law Gazette No. 63, item 638, 2001);

Act, dated December 19<sup>th</sup>, 2002 on behalf of changes of act about wastes and changes in other acts (Law Gazette No. 7, item 78, 2003);

Act, dated July 29<sup>th</sup>, 2005 on behalf of changes of act about wastes and changes in other acts (Law Gazette No. 175, item 1458, 2005)

## 13 HADLING WITH WASTES

### The way of excess amount removal or waste disposal

Do not dispose with communal wastes; do not pour to drainage system. Burn in specially adapted installations or deliver to authorized waste collector.

08 01 Post production, preparation, handling and post use waste, lacquer and paint disposal.

08 01 11\* Lacquer and paint waste, containing organic solvents or another dangerous substances – dangerous waste.

### The way of used packing disposal

Code of waste:

15 01 10\* Packing containing residues of dangerous substances or packing contaminated with dangerous substances.

Used packing should be delivered to authorized collector who has due permission within the range of waste management and especially in dangerous waste management.

Legal basis:

Act, dated April 27<sup>th</sup>, 2001 about wastes (Law Gazette, No. 62, item 628, 2001);

# MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*

Order of Minister of Environment, dated September 27<sup>th</sup>, 2001, on behalf of catalog of wastes (Law Gazette No. 112, item 1206, dated October 8<sup>th</sup>, 2001);

Act, dated May 11<sup>th</sup>, 2001 on behalf of packing and pack wastes (Law Gazette No. 63, item 638, 2001);

Act, dated December 19<sup>th</sup>, 2002 on behalf of changes of act about wastes and changes in other acts (Law Gazette No. 7, item 78, 2003);

Act, dated July 29<sup>th</sup>, 2005 on behalf of changes of act about wastes and changes in other acts (Law Gazette No. 175, item 1458, 2005)

---

## 14 INFORMATION ABOUT TRANSPORT

### 14.1 Classification and packing in transport.

<b>Road and railway transport ADR/RID i GGVS/GGVE:</b>	
Class ADR/RID – GGVS/E	<b>2 5F Thickeners, condensed or disengaged under pressure gases.</b>
Un number	<b>1950</b>
Product name	<b>1950 aerosole</b>
<b>Sea transport IMDG/GGVSee:</b>	
Class IMDG/GGVSee	<b>2</b>
Numer UN	<b>1950</b>
Label	<b>2.1</b>
Number EMS	<b>F-D, S-U</b>
Sea pollutant	<b>No</b>
Technical name	<b>Aerosols</b>
<b>Air transport CIAO-TI i IATA-DGR:</b>	
Klasa CIAO/IATA	<b>2.1</b>
Number UN/ID	<b>1950</b>
label	<b>2.1</b>
Technical name	<b>Aerosols, flammable</b>

---

## 10 INFORMATION CONCERNING THE LAW REGULATIONS

### 15.1 Packages

Packages marking:

Sticker containing:

**INTER TROTON MASTER MATT BLACK**

**MARKING**

**Xi**

**F+**

# MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*



IRRITATING



EXTREMELY  
FLAMMABLE

Phrases indicating  
thread type:

R12	Extremely flammable
R36	Irritating to eyes .
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Phrases indicating conditions  
of safe use:

S2	Keep out of the reach of children.
S23	Do not breathe gas/fumes/vapor/spray.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

**VOC= 800g/l**  
**2004/42/WE IIB(e) (840) 800**

*Pressurized container:*

*Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – no smoking. Keep out of the reach of children.*

## 15.2 Other regulations, if apply:

- Act on behalf of substances and chemical preparations, dated January 11<sup>th</sup>, 2001 (Law Gazette No. 11, item 84; No. 100, item 1085; No. 123, item 1350; No. 127, item 1367 with amendment , dated July 5<sup>th</sup>, 2002 (Law Gazette No. 142, item 1187);
- Order of Minister of Health, dated July 3<sup>rd</sup>, 2002 on behalf of Sheet of characteristic of dangerous substance and dangerous preparation (Law Gazette No. 140, item 1171);
- Order of Minister of Health, dated December 14<sup>th</sup>, 2004 which changes the order on behalf of Sheet of characteristic of dangerous substance and dangerous preparation (Law Gazette No. 2, item 8);
- Order of Minister of Health, dated September 28<sup>th</sup>, 2005 on behalf of list of dangerous substances with their classification and marking (Law Gazette No. 201, item 1674);

## MATERIAL SAFETY DATA SHEET

*This Safety Material Data Sheet is prepared on the base of Regulation 1907/2006/EC of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/WE and repealing Council Regulation 793/93/EEC and Commission Report 1488/94/EC and Council Directive 76/769/EEC and Directives 91/155/EEC, 93/67/EEC, 93/105/EC i 200/21/EC.*

- Order of Minister of Health, dated September 2<sup>nd</sup>, 2003 on behalf of markings on packing of dangerous substances and chemical preparations (Law Gazette No. 173, item 1679 with later amendments);
- Order of Minister of Health, dated September 2<sup>nd</sup>, 2003 on behalf of criteria and methods of classification of substances and chemical preparations (Law Gazette No. 171, item 1666 with later amendments);
- Act, dated April 27<sup>th</sup>, 2001 about waste (Law Gazette No 62, item 628) and Order of Minister of Environment, dated September 27<sup>th</sup>, 2001 on behalf of catalog of waste (Law Gazette No. 112, item 1209);
- Act, dated July 29<sup>th</sup>, 2005 on behalf of changes of Act about wastes and about the changes of some other acts (Law Gazette No. 175, item 1458, 2005);
- Order of Minister of Labor and Social Policy, dated November 29<sup>th</sup>, 2002 on behalf of maximum permissible concentrations and intensity of harmful factors in work environment (Law Gazette No 217, item 1833, 2002 with later amendments).
- Ordinance of Minister for Labour and Social Policy of 29<sup>th</sup> November 2002 in the Matter of Admissible Concentrations and Intensity of Factors Harmful for Health in Workplace Environment (Official Journal No 217 Pos. 1833, 2002 with subsequent modifications)
- Ordinance of Minister for Economy of 16<sup>th</sup> January 2007. In the Matter of Detailed Requirements for Limitation of Emission of Volatile Organic Compounds due to the use of Organic Solvents in Certain Paints and Varnishes and Vehicle Refinishing Products. 72)

---

### 16 OTHER INFORMATION

---

The purpose of information stated in this sheet is to describe the product only from the point of view of work safety requirements. User of this product bears the responsibility for making conditions of safe application of product and he is solely responsible for results of improper use of this product.

**R phrases (indicating type of threat) used in Section 2 of Characteristic Sheet):**

R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R22	Harmful in swallowed.
R36	Irritating to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness.